MOELLER MARINE PRODUCTS CO. 801 NORTH SPRING ST. SPARTA; TENN.; 38583 USA

PRODUCT: 13004-14-019/5 025802 GREEN ZINC PHOSPATE







Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR: MANUFACTURER

MOELLER MARINE PRODUCTS CO. 801 NORTH SPRINGS ST

SPARTA TENN. 38583 USA 931-738-8090

13004-14-019/5 025802 GREEN ZINC PHOSPATE ALKYD BASED COATING. NOT APPLICABLE.

PRODUCT NAME......CHEMICAL FAMILY.....MOLECULAR WEIGHT.....

MIXTURE.

CHEMICAL FORMULA....TRADE NAMES & SYNONYMS..... 13004-14-019/5 025802 GREEN ZINC PHOSPATE

PRODUCT USES..... PRIMER.

Sect	ion 02:	COMPOSITION/IN	FORMATION INGF	REDIENTS

	, <u>0</u>			(LD L () ()	
Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route, Species	LC/50 Route,Species
ACETONE	15-40	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
TOLUENE	7-13	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
XYLENE	3-7	100 ppm	1330-20-7	4.3 g/kg ORAL - RAT	6350 ppm (4 hr) INHAL - RAT
ZINC PHOSPHATE	3-7	10 mg/kg	7779-90-0	NOT AVAILABLE	NOT APPLICABLE
PROPYLENE GLYCOL METHYL ETHER ACETATE	1-5	N/E	108-65-6	8500 mg/kg ORAL - RAT	>4345 ppm (6 hr) INHAL - RAT
VM&P NAPHTHA	1-5	300 ppm	64742-89-8	NOT AVAILABLE	3400 ppm (4 hr) INHAL - RAT
ETHYLBENZENE	0.1-1.0	100 ppm	100-41-4	5460 mg/kg ORAL-RAT	NOT AVAILABLE
PROPANE	5-10	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE
ISOBUTANE	10-30	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

FLAMMABILITY...

INGESTION.....

MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS. INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE INHAI ATION

ASPHYXIANT.

MAY CAUSE IRRITATION. EYE CONTACT..

MAY CAUSE IRRITATION.

SKIN CONTACT......EFFECTS OF ACUTE EXPOSURE.......EFFECTS OF CHRONIC EXPOSURE.....

DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES. SOLVENTS MAY CAUSE DEFATTING DERMATITIS

EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15

MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR.

IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C).....

SPECIAL PROCEDURES.....

WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE

EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A

FIRE INVOLVING THIS MATERIAL.

EXTREMELY FLAMMABLE

00006092	MATERIAL SAFETY DATA SHEET Page 2
PRODUCT: 13004-14-019/5 025802 GRI	EEN ZINC PHOSPATE
Section	05: FIRE FIGHTING MEASURES
UPPER FLAMMABLE LIMIT(% BY VOLUME) LOWER FLAMMABLE LIMIT(% BY VOLUME)	
ÈXPLOSION DATA SENSITIVITY TO STATIC DISCHARGE SENSITIVITY TO IMPACT	NOT APPLICABLE.
PRODUCTS	HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
FLASHBACK	
Section 06:	ACCIDENTAL RELEASE MEASURES
LEAK/SPILL	REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.
Section	07: HANDLING AND STORAGE
ENGINEERING CONTROLS	KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C. NONE KNOWN.
Section 08: EXPO	OSURE CONTROLS/PERSONAL PROTECTION
GLOVES/ TYPERESPIRATORY/TYPE	WEAR CHEMICAL RESISTANT GLOVES. IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. SAFETY GLASSES.
EYE/IYPEOTHER/TYPEOTHER/TYPE	NOT NORMALLY REQUIRED.
Section 09: P	HYSICAL AND CHEMICAL PROPERTIES
PHYSICAL STATEAPPEARANCEODORODOR THRESHOLDVAPOUR PRESSURE(PSIG)-AEROSOL	YELLOW OR GREEN. KETONE. NOT AVAILABLE.
BOILING POINT (°C)(CONC) EVAPORATION RATE n-BUTYL ACETATE = 1 VAPOUR DENSITY (AIR=1)	GREATER THAN 1.
(BY WEIGHT) SOLUBILITY IN WATER g/L (20°C) PH SPECIFIC GRAVITY (LIQUID) COEFFICIENT OF WATER\OIL DIST FREEZING POINT: (°C)	NOT AVAILABLE. NOT APPLICABLE. 0.92-0.96. NOT AVAILABLE.
, ,	10: STABILITY AND REACTIVITY
HAZARDOUS PRODUCTS OF	HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CHEMICAL STABILITY: YESNO, WHICH CONDITIONS?	UNDER NORMAL CONDITIONS
COMPATIBILITY WITH OTHER SUBSTANCES: NO, WHICH ONES? REACTIVITY CONDITIONS? HAZARDOUS POLYMERIZATION	NOT APPLICABLE.
Section 11	: TOXICOLOGICAL INFORMATION
IRRITANCY OF MATERIAL	
SENSITIZING CAPABILITY OF MATERIAL	UNKNOWN. THE INGREDIENTS OF THIS PRODUCT ARE NOT LISTED AS CARCINOGENS BY NTP, (NATIONAL TOXICOLOGY PROGRAM), NOT REGULATED AS CARCINOGENS BY OSHA, (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION), AND HAVE NOT BEEN EVALUATED BY IARC,(INTERNATIONAL AGENCY FOR RESEARCH ON CANCER), NOR BY ACGIH (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS).

00006092	MATERIAL SAFETY DATA SHEET Page
PRODUCT: 13004-14-019/5 025802 GRE	EEN ZINC PHOSPATE
Section 11	: TOXICOLOGICAL INFORMATION
TERATOGENICITY	NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE
MUTAGENICITY	ANTICIPATED. NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE
	ANTICIPATED.
Section 12	: ECOLOGICAL CONSIDERATIONS
ENVIRONMENTAL	NOT AVAILABLE.
Section 1	13: DISPOSAL CONSIDERATIONS
WASTE DISPOSAL	DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.
Section 14	: TRANSPORTATION INFORMATION
T.D.G. CLASSIFICATIOND.O.T. CLASSIFICATION	CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1) . CONSUMER COMMODITY, ORM-D.
Section 1	15: REGULATORY INFORMATION
CANADIAN REGULATIONS:	
WHMIS CLASSIFICATION	
CNFC SECTION 3.3.5CEPA (Canadian Environmental Protection Act)	ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC
U.S. REGULATIONS:	SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.
HMIS RATING HEALTH HMIS RATING FLAMMABILITY HMIS RATING REACTIVITY HMIS RATING PERSONAL PROTECTION NFPA CODE 30B	4 SEVERE HAZARD. 0 MINIMAL HAZARD. B. LEVEL 2. THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986: WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA
SARA 313 INFORMATION:	TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. CAS #: CHEMICAL NAME: *100-41-4 ETHYL BENZENE IN XYLENE *108-88-3 TOLUENE THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: CAS #: CHEMICAL NAME: *100-41-4 ETHYL BENZENE *108-88-3 TOLUENE .*1330-20-7 XYLENE
TSCA (Toxic Substances Control Act)	ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY
V.O.C.(M.I.R.)	IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING. COMPLIES WITH AVIATION AND MARINE PRIMER CATERGORY <2 g OZONE / g PRODUCT.
Section	on 16: OTHER INFORMATION
	THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY MOELLER MARINE INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. MOELLER MARINE INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. TECHNICAL SERVICES May28/12