MOELLER MARINE PRODUCTS CO. 801 NORTH SPRING ST. SPARTA; TENN.; 38583 USA

PRODUCT: 13004-14-033/5 025801 YELLOW ZINC PHOSPHATE







Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR: MANUFACTURER

MOELLER MARINE PRODUCTS CO. 801 NORTH SPRINGS ST

SPARTA TENN. 38583 USA 931-738-8090

13004-14-033/5 025801 YELLOW ZINC PHOSPHATE ALKYD BASED COATING. NOT APPLICABLE.

PRODUCT NAME......CHEMICAL FAMILY.....MOLECULAR WEIGHT.....

MIXTURE.

CHEMICAL FORMULA....TRADE NAMES & SYNONYMS..... 13004-14-033/5 025801 YELLOW ZINC PHOSPHATE

PRODUCT USES..... PRIMER.

FORMULA/LAB BOOK #..... F 14-533A/002-21-299.

ents	%	Exposure Limit	C.A.S.#	LD/50, Route,Spec		

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ACETONE	15-40	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
TOLUENE	7-13	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
XYLENE	3-7	100 ppm	1330-20-7	4.3 g/kg ORAL - RAT	6350 ppm (4 hr) INHAL - RAT
PROPYLENE GLYCOL METHYL ETHER ACETATE	5-10	N/E	108-65-6	8500 mg/kg ORAL - RAT	>4345 ppm (6 hr) INHAL - RAT
VM&P NAPHTHA	1-5	300 ppm	64742-89-8	NOT AVAILABLE	3400 ppm (4 hr) INHAL - RAT
ZINC PHOSPHATE	3-7	10 mg/kg	7779-90-0	NOT AVAILABLE	NOT APPLICABLE
ETHYLBENZENE	0.1-1.0	100 ppm	100-41-4	5460 mg/kg ORAL-RAT	NOT AVAILABLE
PROPANE	5-10	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE
ISOBUTANE	10 - 30	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

FLAMMABILITY...

INGESTION.....

MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS. INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE INHAI ATION

ASPHYXIANT.

MAY CAUSE IRRITATION. EYE CONTACT..

SKIN CONTACT......EFFECTS OF ACUTE EXPOSURE.......EFFECTS OF CHRONIC EXPOSURE..... MAY CAUSE IRRITATION.

DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES. SOLVENTS MAY CAUSE DEFATTING DERMATITIS

EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15

MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR.

IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C).....

WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE SPECIAL PROCEDURES.....

EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A

FIRE INVOLVING THIS MATERIAL.

EXTREMELY FLAMMABLE.

IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

00006091	MATERIAL SAFETY DATA SHEET Page 2
PRODUCT: 13004-14-033/5 025801 YEL	1 05: FIRE FIGHTING MEASURES
UPPER FLAMMABLE LIMIT (% BY VOLUME) LOWER FLAMMABLE LIMIT (% BY VOLUME)	
EXPLOSION DATA SENSITIVITY TO STATIC DISCHARGE SENSITIVITY TO IMPACT HAZARDOUS COMBUSTION	NOT APPLICABLE.
PRODUCTS AEROSOL FLAME PROJECTION CLASSIFIED AS:	HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
	ACCIDENTAL RELEASE MEASURES
	REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.
Section	07: HANDLING AND STORAGE
	KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
ENGINEERING CONTROLS	VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
Section 08: EXP	OSURE CONTROLS/PERSONAL PROTECTION
GLOVES/ TYPERESPIRATORY/TYPE	WEAR CHEMICAL RESISTANT GLOVES. IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. SAFETY GLASSES.
EYE/TYPE FOOTWEAR/TYPE OTHER/TYPE	NOT NORMALLY REQUIRED.
Section 09: P	PHYSICAL AND CHEMICAL PROPERTIES
PHYSICAL STATE APPEARANCE ODOR ODOR THRESHOLD VAPOUR PRESSURE(PSIG)-AEROSOL	YELLOW OR GREEN. KETONE. NOT AVAILABLE.
@ 20 C BOILING POINT (°C)(CONC) EVAPORATION RATE n-BUTYL ACETATE = 1	57 - 150. GREATER THAN 1.
VAPOUR DENSITY (AIR=1) (BY WEIGHT) SOLUBILITY IN WATER q/L (20°C)	NOT AVAILABLE.
pHSPECIFIC GRAVITY (LIQUID) COEFFICIENT OF WATER\OIL DIST FREEZING POINT: (°C)	NOT APPLICABLE. 0.92-0.96. NOT AVAILABLE.
, ,	10: STABILITY AND REACTIVITY
HAZARDOUS PRODUCTS OF	HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CHEMICAL STABILITY: YES NO, WHICH CONDITIONS?	UNDER NORMAL CONDITIONS.
COMPATIBILITY WITH OTHER SUBSTANCES: NO, WHICH ONES? REACTIVITY CONDITIONS?HAZARDOUS POLYMERIZATION	NOT APPLICABLE.
Section 11	1: TOXICOLOGICAL INFORMATION
REPRODUCTIVE EFFECTS	XYLENE - HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT LEVELS TOXIC TO THE MOTHER, AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN. TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE ADVERSE FETAL DEVELOPMENTAL EFFECTS. SKIN/EYE IRRITANT.
SENSITIZING CAPABILITY OF MATERIAL	UNKNOWN. XYLENE - THIS PRODUCT CONTAINS ETHYLBENZENE (ETHYLBENZENE IS IN XYLENE). ETHYLBENZENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS. TOXICITY TESTS CARRIED OUT FOR CHRONIC EFFECTS AND MUTAGENICITY HAVE BEEN NEGATIVE. THE RELEVANCE OF THIS FINDING TO HUMANS IS UNCERTAIN. IARC HAS CLASSIFIED ETHYBENZENE AS A POSSIBLE HUMAN CARCINOGEN.

00006091	MATERIAL SAFETY DATA SHEET Pa	age 3
PRODUCT: 13004-14-033/5 025801 YEI	LLOW ZINC PHOSPHATE	
Section 1	1: TOXICOLOGICAL INFORMATION	
TERATOGENICITY	NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.	
MUTAGENICITY	NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE ANTICIPATED.	
Section 12	2: ECOLOGICAL CONSIDERATIONS	
ENVIRONMENTAL	NOT AVAILABLE.	
Section	13: DISPOSAL CONSIDERATIONS	
WASTE DISPOSAL	DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.	
Section 14	4: TRANSPORTATION INFORMATION	
T.D.G. CLASSIFICATION	CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1) . CONSUMER COMMODITY, ORM-D.	
Section	15: REGULATORY INFORMATION	
CANADIAN REGULATIONS:		
WHMIS CLASSIFICATIONCNFC SECTION 3.3.5CEPA (Canadian Environmental Protection Act)		
U.S. REGULATIONS:	ODD TARGED LIGH (BOL) ON THE NOT REGORDED TO BE LIGHED.	
HMIS RATING HEALTH	4 SEVERE HAZARD. 0 MINIMAL HAZARD. B. LEVEL 2. THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: CAS #: CHEMICAL NAME: *108-88-3 TOLUENE	3
CALIFORNIA PROPOSITION 65:	.*1330-20-7 .*100-41-4 ETHYL BENZENE THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAIDRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986: WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNITO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. CAS #: CHEMICAL NAME: *100-41-4 ETHYL BENZENE IN XYLENE	
,	*108-88-3 TOLUENE . ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY	
V.O.C.(M.I.R.)	IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING. COMPLIES WITH AVIATION AND MARINE PRIMER CATERGORY <2 g OZONE / g PRODUCT.	
Secti	on 16: OTHER INFORMATION	
PREPARED BY		USE E IC